



NOTES

1. MATERIAL: UVFS
2. CLEAR APERTURE: 22 mm
3. CENTER APERTURE: 581 nm
4. FWHM: 28 nm
5. TRANSMITTED WAVEFRONT: $\lambda @ 633 \text{ nm}$
6. SURFACE QUALITY: 60/40(S/D)
7. COATING: BANDPASS FILTER, 0° AOI
 $T_{\text{abs}} \geq 90\%$, $T_{\text{avg}} \geq 93\% @ 570 \text{ nm} - 592 \text{ nm}$, 0° AOI,
 $OD_{\text{abs}} \geq 5 @ 300 \text{ nm} - 561 \text{ nm} \& 601 \text{ nm} - 1100 \text{ nm}$, 0° AOI,

DRAWING PROJECTION			LBTEK			
	NAME	DATE	ET580/25x			
DRAWN	LZHOU	JUL ./1st/24	PREMIUM BANDPASS FILTER $\phi 25 \text{ mm}$, CWL=581 nm, FWHM=28 nm			
APPROVAL	WCHENG	JUL ./1st/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			UVFS	1.5 g	2:1	A