



NOTES

1. DESIGN WAVELENGTH: 486.1 nm, 587.6 nm & 656.3 nm
2. CLEAR APERTURE: >90%CA
3. OPERATION WAVELENGTH: 400 nm-700 nm
4. DIAMETER TOLERANCE: +0.0/-0.1 mm
5. THICKNESS TOLERANCE: ±0.1 mm
6. FOCAL LENGTH: 80.0 mm ± 1% @ 587.6 nm
7. BACK FOCAL LENGTH(REF): 75.3 mm
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE POWER(S1, S2):  $3\lambda/2$  @ 632.8 nm
10. SURFACE IRREGULARITY(S1, S2):  $\lambda/4$  @ 632.8 nm
11. CENTRATION: < 3 arcmin
12. CHAMFER: < 0.2 mm, 45°
13. COATING(S1, S2): AR COATING  $R_{avg}$  < 0.5% @ 400 nm-700 nm

	MATERIAL
①	N-BK7
②	N-SF5

DRAWING PROJECTION				<b>LBTEK</b>			
	NAME	DATE	AD407-A				
DRAWN	BSHU	Aug./1st/24	$\phi$ 25.4 mm, F=80.0 mm ACHROMATIC DOUBLETS AR COATING 400-700 nm				
APPROVAL	WCHENG	Aug./1st/24	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7/N-SF5	34.64g	10:1	A	