



NOTES

1. DESIGN WAVELENGTH: 1016.0 nm, 1330.0 nm & 1550.0 nm
2. CLEAR APERTURE: $>90\%CA$
3. OPERATION WAVELENGTH: 1100 nm-1650 nm
4. DIAMETER TOLERANCE: $+0.0/-0.1\text{ mm}$
5. THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
6. FOCAL LENGTH: $60.0\text{ mm} \pm 1\% @ 1330.0\text{ nm}$
7. BACK FOCAL LENGTH(REF): 50.5 mm
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE POWER(S1, S2): $3\lambda/2 @ 632.8\text{ nm}$
10. SURFACE IRREGULARITY(S1, S2): $\lambda/4 @ 632.8\text{ nm}$
11. CENTRATION: $<3\text{ arcmin}$
12. CHAMFER: $<0.2\text{ mm}, 45^\circ$
13. COATING(S1, S2): AR COATING $R_{avg} < 0.5\% @ 1100\text{ nm}-1650\text{ nm}$

	MATERIAL
①	N-LAK22
②	N-SF6HT

DRAWING PROJECTION				LBTEK			
	NAME	DATE	AD417-C				
DRAWN	BSHU	Aug./5th/24	$\phi 25.4\text{ mm}, F=60.0\text{ mm}$ ACHROMATIC DOUBLETS AR COATING 1100-1650 nm				
APPROVAL	WCHENG	Aug./5th/24	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-LAK22/N-SF6	4.40g	2:1	A	