



NOTES

1. DESIGN WAVELENGTH: 706.5 nm, 855.0 nm & 1015.0 nm
2. CLEAR APERTURE: >90%CA
3. OPERATION WAVELENGTH: 700 nm-1100 nm
4. DIAMETER TOLERANCE: +0.0/-0.1 mm
5. THICKNESS TOLERANCE: ±0.1 mm
6. FOCAL LENGTH: 1000.0 mm ±1% @ 855.0 nm
7. BACK FOCAL LENGTH(REF): 993.6 mm
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE POWER(S1, S2):  $3\lambda/2$  @ 632.8 nm
10. SURFACE IRREGULARITY(S1, S2):  $\lambda/4$  @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1, S2): AR COATING  $R_{avg}$  <0.5% @ 700 nm-1100 nm

	MATERIAL
①	N-BAF10
②	SF10

DRAWING PROJECTION				<b>LBTEK</b>			
	NAME	DATE	AD529-B				
DRAWN	BSHU	Aug./5th/24	$\phi$ 50.8 mm, F=1000.0 mm ACHROMATIC DOUBLETS AR COATING 700-1100 nm				
APPROVAL	WCHENG	Aug./5th/24	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BAF10/N-SF10	13.62g	1:1	A	