



NOTES

1. DESIGN WAVELENGTH: 1016.0 nm, 1330.0 nm & 1550.0 nm
2. CLEAR APERTURE: >90 %CA
3. OPERATION WAVELENGTH: 1050 nm-1700 nm
4. FOCAL LENGTH: 10.0 mm ± 1% @ 1330.0 nm
5. BACK FOCAL LENGTH (REF) : 6.9 mm
6. SURFACE QUALITY (S/D) : 40/20
7. SURFACE POWER (S1, S2) : $3\lambda/2$ @ 632.8 nm
8. SURFACE IRREGULARITY (S1, S2) : $\lambda/4$ @ 632.8 nm
9. CENTRATION: <3 arcmin
10. CHAMFER: <0.2 mm, 45°
11. AR COATING (S1, S2) : $R_{avg} < 0.5\%$ @ 1050 nm-1700 nm

	MATERIAL
①	N-LAK22
②	N-SF6

DRAWING PROJECTION			LBTEK			
	NAME	DATE	AD901-C			
DRAWN	SHAN	SEP./12th/25	ACHROMATIC DOUBLETS			
APPROVAL	WCHENG	SEP./12th/25	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-LAK22/N-SF6	0.26g	10:1	A