



NOTES

1. DESIGN WAVELENGTH: 706.5 nm, 855.0 nm & 1015.0 nm
2. CLEAR APERTURE: >90 %CA
3. OPERATION WAVELENGTH: 650 nm-1050 nm
4. FOCAL LENGTH: 7.5 mm ± 1% @ 855.0 nm
5. BACK FOCAL LENGTH (REF) : 4.8 mm
6. SURFACE QUALITY (S/D) : 40/20
7. SURFACE POWER (S1, S2) : $3\lambda/2$ @ 632.8 nm
8. SURFACE IRREGULARITY (S1, S2) : $\lambda/4$ @ 632.8 nm
9. CENTRATION: <3 arcmin
10. CHAMFER: <0.2 mm, 45°
11. AR COATING (S1, S2) : $R_{avg} < 0.5\%$ @ 650 nm-1050 nm

	MATERIAL
①	N-BAF10
②	N-SF6HT

DRAWING PROJECTION				LBTEK			
	NAME	DATE	AD923-B				
DRAWN	SHAN	SEP./12th/25	ACHROMATIC DOUBLETS				
APPROVAL	WCHENG	SEP./12th/25	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BAF10/N-SF6HT	0.29g	10:1	A	