



NOTES

1. DESIGN WAVELENGTH: 706.5 nm, 855.0 nm & 1015.0 nm
2. CLEAR APERTURE: >90%CA
3. OPERATION WAVELENGTH: 700 nm-1100 nm
4. DIAMETER TOLERANCE: +0.0/-0.1 mm
5. THICKNESS TOLERANCE: ±0.1 mm
6. FOCAL LENGTH: -40.0 mm±1%@855.0 nm
7. BACK FOCAL LENGTH(REF): -43.4 mm
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S1,S2):  $3\lambda/2@632.8\text{ nm}$
10. SURFACE IRREGULARITY(S1,S2):  $\lambda/4@632.8\text{ nm}$
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): AR COATING  $R_{avg}<0.5\%@700\text{ nm}-1100\text{ nm}$

	MATERIAL
①	N-BAF10
②	N-SF6HT

DRAWING PROJECTION		<b>LBTEK</b>				
		ADN415-B				
DRAWN	BSHU	DATE	$\phi 25.4\text{ mm}, F=-40.0\text{ mm}$ ACHROMATIC DOUBLETS AR COATING 700-1100 nm			
APPROVAL	WCHENG	Aug./5th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BAF10/N-SF6HT	3.98g	2:1	A