



NOTES

1. FIBER TYPE: 1064-XP
2. OPERATION WAVELENGTH: 950 nm-1010 nm
3. WORKING DISTANCE: 15 mm
4. BEAM DIAMETER: ≤ 0.6 mm
5. INSERTION LOSS: ≤ 0.5 dB
6. MAXIMUM OPTICAL POWER: 300 mW
7. OPERATING TEMPERATURE: 0-70°C
8. PAIRING LOSS: 1.0 dB

The temperature measurement environment is 25° C, The above test data does not include connectors, if the connectors are added, the insertion loss will increase by 0.6dB, and the return loss will decrease by 5dB.

| | | | | | | |
|--|--------|--------------|--|--------|-------|-----|
| DRAWING PROJECTION | | | LBTEK | | | |
| | | | | | | |
| | NAME | DATE | DGFC-980-FCAPC | | | |
| DRAWN | BSHU | Aug./26th/24 | LENGTH: 1m, JOINT: FC/APC WAVELENGTH: 950-1010 nm | | | |
| APPROVAL | WCHENG | Aug./26th/24 | MATERIAL | WEIGHT | SCALE | REV |
| FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES | | | OXIDE GLASS | 7 g | 1:1 | A |