



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 420 nm-2.3  $\mu$ m
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE:  $\pm$ 0.1 mm
5. FOCAL LENGTH: -25.0 mm  $\pm$ 1%
6. BACK FOCAL LENGTH(REF): -25.6 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2):  $3\lambda/2$  @ 632.8 nm
10. SURFACE IRREGULARITY(S2):  $\lambda/4$  @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): UNCOATED

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE				
DRAWN	BSHU	JUL./29th/24	$\phi$ 25.4 mm, F=-25.0 BI-CONCAVE LENS UNCOATED			
APPROVAL	WCHENG	JUL./29th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-SF11	6.33g	2:1	A