



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 1100 nm-1650 nm
3. DIAMETER TOLERANCE:  $+0.0/-0.1\text{ mm}$
4. THICKNESS TOLERANCE:  $\pm 0.1\text{ mm}$
5. FOCAL LENGTH:  $10.0\text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): 9.2 mm
7. CLEAR APERTURE:  $>90\%CA$
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2):  $3\lambda/2 @ 632.8\text{ nm}$
10. SURFACE IRREGULARITY(S2):  $\lambda/4 @ 632.8\text{ nm}$
11. CENTRATION:  $<3\text{ arcmin}$
12. CHAMFER:  $<0.2\text{ mm}, 45^\circ$
13. COATING(S1,S2):  $r_{avg} \leq 0.5\% @ 1100\text{ nm}-1650\text{ nm}$

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE	BCX10001-C			
DRAWN	BSHU	JUL./29th/24	$\phi 6.0\text{ mm}, F=10.0\text{ mm}$ BI-CONVEX LENS AR:1100 nm-1650 nm			
APPROVAL	WCHENG	JUL./29th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	0.13g	10:1	A