



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350 nm-2.0 μm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: 200.0 mm±1%
6. BACK FOCAL LENGTH(REF): 199.1 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2): $3\lambda/2$ @ 632.8 nm
10. SURFACE IRREGULARITY(S2): $\lambda/4$ @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): UNCOATED

| | | | | | | |
|--|--------|--------------|--|--------|-------|-----|
| DRAWING PROJECTION | | | LBTEK | | | |
| | NAME | DATE | | | | |
| DRAWN | BSHU | JUL./29th/24 | ϕ 25.4 mm, F=200.0 mm BI-CONVEX LENS UNCOATED | | | |
| APPROVAL | WCHENG | JUL./29th/24 | MATERIAL | WEIGHT | SCALE | REV |
| FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES | | | N-BK7 | 2.96g | 10:1 | A |