



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350 nm-2.0 μ m
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: \pm 0.1 mm
5. FOCAL LENGTH: 250.0 mm \pm 1%
6. BACK FOCAL LENGTH(REF): 249.1 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2): $3 \lambda / 2 @ 632.8 \text{ nm}$
10. SURFACE IRREGULARITY(S2): $\lambda / 4 @ 632.8 \text{ nm}$
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): UNCOATED

DRAWING PROJECTION			LBTEK			
	NAME	DATE	BCX10618			
DRAWN	BSHU	JUL./29th/24	ϕ 25.4 mm, F=250.0 mm BI-CONVEX LENS UNCOATED			
APPROVAL	WCHENG	JUL./29th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	2.86g	10:1	A