



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 1100 nm-1650 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ± 0.1 mm
5. FOCAL LENGTH: 75.0 mm $\pm 1\%$
6. BACK FOCAL LENGTH(REF): 72.1 mm
7. CLEAR APERTURE: $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1,S2): 20/10
9. SURFACE POWER(S1S2): $3\lambda/2 @ 632.8$ nm
10. SURFACE IRREGULARITY(S1S2): $\lambda/4 @ 632.8$ nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): AR COATING $R_{avg} \leq 0.5\% @ 1100$ nm-1650 nm

DRAWING PROJECTION			LBTEK			
	NAME	DATE	BFCX10612-C			
DRAWN	BSHU	JUL./29th/24	$\phi 25.4$ mm, $f=75$ mm BEST FORM LENS AR COATING 1100-1650 nm			
APPROVAL	WCHENG	JUL./29th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	4.87g	2:1	A