



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350 nm-2.0  $\mu\text{m}$
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE:  $\pm 0.1$  mm
5. FOCAL LENGTH: 200 mm  $\pm 1\%$
6. BACK FOCAL LENGTH(REF): 197 mm
7. CLEAR APERTURE:  $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1,S2): 20/10
9. SURFACE POWER(S1S2):  $3\lambda/2 @ 632.8$  nm
10. SURFACE IRREGULARITY(S1S2):  $\lambda/4 @ 632.8$  nm
11. CENTRATION:  $<3$  arcmin
12. CHAMFER:  $<0.2$  mm,  $45^\circ$
13. COATING(S1,S2): UNCOATED

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE	BFCX10617			
DRAWN	BSHU	JUL./29th/24	$\phi 25.4$ mm, f=200 mm BEST FORM LENS UNCOATING			
APPROVAL	WCHENG	JUL./29th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	4.46g	2:1	A