



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 200 nm-2.1 μ m
3. DIAMETER TOLERANCE: +0.0/-0.2 mm
4. THICKNESS TOLERANCE: \pm 0.2 mm
5. FOCAL LENGTH: -100.0 mm \pm 1%
6. BACK FOCAL LENGTH(REF): -102.4 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2$ @ 632.8 nm
10. SURFACE POWER(S2): $3 \lambda/2$ @ 632.8 nm
11. SURFACE IRREGULARITY(S2): $\lambda/2$ @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): UNCOATED

DRAWING PROJECTION			LBTEK			
	NAME	DATE	CC20613			
DRAWN	LTAN	JUN./22th/25	ϕ 25.4 mm, f=-100.0 mm PLANO CONCAVE LENS UNCOATED			
APPROVAL	WCHENG	JUN./22th/25	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			UVFS	4.9 g	2:1	A