



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 700 nm-1100 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: -30.0 mm±1%
6. BACK FOCAL LENGTH(REF): -32.0 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2$ @ 632.8 nm
10. SURFACE POWER(S2): $3\lambda/2$ @ 632.8 nm
11. SURFACE IRREGULARITY(S2): $\lambda/4$ @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): AR COATING Ravg <0.5% @ 700 nm-1100 nm

DRAWING PROJECTION			LBTEK			
	NAME	DATE	ϕ 25.4 mm, f=-30.0 mm PLANO CONCAVE LENS AR COATING 700-1100nm			
DRAWN	BSHU	JUL./29th/24	MATERIAL	WEIGHT	SCALE	REV
APPROVAL	WCHENG	JUL./29th/24	N-SF11	6.58g	10:1	A
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES						