



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm-700 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
5. FOCAL LENGTH: $f=15.0\text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=13.6\text{ mm}$
7. CLEAR APERTURE: $>85\%CA$
8. SURFACE QUALITY(S/D) (S1, S2) : 40/20
9. SURFACE FLATNESS (S1) : $\lambda/2 @ 632.8\text{ nm}$
10. SURFACE POWER (S2) : $3\lambda/2 @ 632.8\text{ nm}$
11. SURFACE IRREGULARITY (S2) : $\lambda/4 @ 632.8\text{ nm}$
12. CENTRATION: $<3\text{ arcmin}$
13. CHAMFER: $<0.2\text{ mm}, 45^\circ$
14. COATING (S1, S2) : AR COATING $R_{avg} < 0.5\% @ 400\text{ nm}-700\text{ nm}$

DRAWING PROJECTION			LBTEK			
	NAME	DATE	CX10003-A			
DRAWN	BSHU	JUL./23th/24	$\phi 6\text{ mm}, f=15\text{ mm}$ PLANO CONVEX LENS AR COATING 400-700 nm			
APPROVAL	WCHENG	JUL./23th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	0.12g	10:1	B