



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm-700 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE:  $\pm 0.1$  mm
5. FOCAL LENGTH:  $f=30.0$  mm  $\pm 1\%$
6. BACK FOCAL LENGTH(REF):  $bf=28.7$  mm
7. CLEAR APERTURE:  $>85\%$  CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1):  $\lambda/2$  @ 632.8 nm
10. SURFACE POWER(S2):  $3\lambda/2$  @ 632.8 nm
11. SURFACE IRREGULARITY(S2):  $\lambda/4$  @ 632.8 nm
12. CENTRATION:  $<3$  arcmin
13. CHAMFER:  $<0.2$  mm,  $45^\circ$
14. COATING(S1, S2): AR COATING  $R_{avg}<0.5\%$  FROM 400 nm-700 nm

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE	CX10007-A			
DRAWN	BSHU	JUL./23th/24	$\varnothing 6$ mm, $f=30$ mm PLANO CONVEX LENS AR COATING 400-700 nm			
APPROVAL	WCHENG	JUL./23th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	0.11g	10:1	B