



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm–700 nm
3. DIAMETER TOLERANCE: +0.0/–0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=20\text{ mm}\pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=18.3\text{ mm}$
7. CLEAR APERTURE: $>85\%CA$
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8\text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8\text{ nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8\text{ nm}$
12. CENTRATION: $<3\text{ arcmin}$
13. CHAMFER: $<0.2\text{ mm}, 45^\circ$
14. COATING(S1,S2): AR COATING $R_{avg}<0.5\% @ 400\text{ nm}–700\text{ nm}$

DRAWING PROJECTION			LBTEK			
	NAME	DATE	CX10204–A			
DRAWN	BSHU	JUL./23th/24	$\varnothing 9\text{ mm}, f=20\text{ mm}$ PLANO CONVEX LENS AR COATING 400–700 nm			
APPROVAL	WCHENG	JUL./23th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N–BK7	0.31 g	5:1	B