



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 532&1064 nm
3. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
4. THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
5. FOCAL LENGTH: $f=30.0\text{mm}\pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=24.2\text{mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8\text{nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8\text{nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8\text{nm}$
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): AR COATING $R_{avg}<0.25\% @ 532\&1064$ nm

DRAWING PROJECTION			LBTEK			
	NAME	DATE				
DRAWN	BSHU	Feb./3rd/24	PLANO CONVEX LENS AR COATING 532&1064 nm			
APPROVAL	WCHENG	Feb./3rd/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	6.89 g	2:1	A