



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm–700 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=50.0 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=46.3 \text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8 \text{ nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: $<3 \text{ arcmin}$
13. CHAMFER: $<0.2 \text{ mm}, 45^\circ$
14. COATING(S1,S2): AR COATING $R_{avg}<0.5\% @ 400 \text{ nm}-700 \text{ nm}$

DRAWING PROJECTION			LBTEK			
	NAME	DATE	$\varnothing 25.4 \text{ mm}, f=50 \text{ mm}$ PLANO CONVEX LENS AR COATING 400–700 nm			
DRAWN	BSHU	JUL./24th/24	MATERIAL	WEIGHT	SCALE	REV
APPROVAL	WCHENG	JUL./24th/24	N-BK7	4.52g	2:1	A
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES						