



注释

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm-700 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=110.0 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=107.3 \text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8 \text{ nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: $<3 \text{ arcmin}$
13. CHAMFER: $<0.2 \text{ mm}, 45^\circ$
14. COATING(S1, S2): AR COATING $R_{avg} < 0.5\% @ 400 \text{ nm}-700 \text{ nm}$

DRAWING PROJECTION			LBTEK			
	NAME	DATE				
DRAWN	BSHU	Feb. /3rd/24	PLANO CONVEX			
APPROVAL	WCHENG	Feb. /3rd/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	1.66g	2:1	A