



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 1100 nm-1650 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE:  $\pm 0.1$  mm
5. FOCAL LENGTH:  $f=150\text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF):  $bf=147.5$  mm
7. CLAEER APERTURE:  $>90\%CA$
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1):  $\lambda/2 @ 632.8$  nm
10. SURFACE POWER(S2):  $3\lambda/2 @ 632.8$  nm
11. SURFACE IRREGULARITY(S2):  $\lambda/4 @ 632.8$  nm
12. CENTRATION:  $<3$  arcmin
13. CHAMFER:  $<0.2$  mm,  $45^\circ$
14. COATING(S1,S2): AR COATING  $R_{avg} < 0.5\% @ 1100\text{ nm}-1650$  nm

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE	CX10615-C			
DRAWN	BSHU	JUL./24th/24	$\varnothing 25.4$ mm, $f=150$ mm PLANO CONVEX LENS AR COATING 1100-1650 nm			
APPROVAL	WCHENG	JUL./24th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	3.18g	2:1	A