



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm-700 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=60\text{ mm}\pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=49.1\text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8\text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8\text{ nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8\text{ nm}$
12. CENTRATION: $<3\text{ arcmin}$
13. CHAMFER: $<0.2\text{ mm}, 45^\circ$
14. COATING(S1,S2): AR COATING $R_{avg} <0.5\% @ 400\text{ nm}-700\text{ nm}$

DRAWING PROJECTION			LBTEK			
	NAME	DATE				
DRAWN	BSHU	JUL./24th/24	$\varnothing 50.8\text{ mm}, f=60\text{ mm}$ PLANO CONVEX LENS AR COATING 400-700 nm			
APPROVAL	WCHENG	JUL./24th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	52.1g	1:1	A