



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 700 nm-1100 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE:  $\pm 0.1$  mm
5. FOCAL LENGTH:  $f=1000.0$  mm  $\pm 1\%$
6. BACK FOCAL LENGTH(REF):  $bf=994.3$  mm
7. CLEAR APERTURE:  $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1.S2): 40/20
9. SURFACE FLATNESS(S1):  $\lambda/2$  @ 632.8 nm
10. SURFACE POWER(S2):  $3\lambda/2$  @ 632.8 nm
11. SURFACE IRREGULARITY(S2):  $\lambda/4$  @ 632.8 nm
12. CENTRATION:  $<3$  arcmin
13. CHAMFER:  $<0.2$  mm,  $45^\circ$
14. COATING(S1,S2): AR COATING  $R_{avg} <0.5\%$  @ 1100 nm-1650 nm

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE	CX10823-B			
DRAWN	BSHU	JUL./24th/24	$\phi 50.8$ mm, $f=1000$ mm PLANO CONVEX LENS AR COATING 700-1100 nm			
APPROVAL	WCHENG	JUL./24th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	16.8g	2:1	A