



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 190 nm-2.1  $\mu$ m
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE:  $\pm$ 0.1 mm
5. FOCAL LENGTH:  $f=20.1$  mm $\pm$ 1%
6. BACK FOCAL LENGTH(REF):  $bf=17.1$  mm
7. CLEAR APERTURE:  $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1):  $\lambda/2$  @ 632.8 nm
10. SURFACE POWER(S2):  $3\lambda/2$  @ 632.8 nm
11. SURFACE IRREGULARITY(S2):  $\lambda/4$  @ 632.8 nm
12. CENTRATION:  $<3$  arcmin
13. CHAMFER:  $<0.2$  mm,  $45^\circ$
14. COATING(S1,S2): UNCOATED

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE	CX20304			
DRAWN	SHAN	JUN./24th/25	$\phi$ 12.7 mm, $f=20.1$ mm PLANO CONVEX LENS UNCOATED			
APPROVAL	WCHENG	JUN./24th/25	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			UVFS	0.97g	5:1	B