



NOTES:

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 700-1100 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THKKNES TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=30.1 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=27.8 \text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1.S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2): $3 \lambda/2 @ 632.8 \text{ nm}$
11. SURFACE RREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: $<3 \text{ arcmin}$
13. CHAMFER: $<0.2 \text{ mm}, 45^\circ$
14. AR COATNG(S1.S2): $R_{avg} < 0.5\% @ 700-1100 \text{ nm}$ (6° AOI , single)

DRAWING PROJECTION			LBTEK			
	NAME	DATE				
DRAWN	AGAO	MAY./21th/25	PLANO CONVEX LENS			
APPROVAL	SHAN	MAY./21th/25	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			UVFS	0.72g	5:1	A