



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350 nm–700 nm
3. DIAMETER TOLERANCE:  $+0.0/-0.1$  mm
4. THICKNESS TOLERANCE:  $\pm 0.1$  mm
5. FOCAL LENGTH:  $f=150.5$  mm  $\pm 1\%$
6. BACK FOCAL LENGTH(REF):  $bf=148.4$  mm
7. CLEAR APERTURE:  $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE FLATNESS(S1):  $\lambda/2$  @ 632.8 nm
10. SURFACE POWER(S2):  $3\lambda/2$  @ 632.8 nm
11. SURFACE IRREGULARITY(S2):  $\lambda/4$  @ 632.8 nm
12. CENTRATION:  $<3$  arcmin
13. CHAMFER:  $<0.2$  mm,  $45^\circ$
14. COATING(S1, S2): AR COATING  $R_{avg} < 0.5\%$  @ 350 nm–700 nm

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE	CX20615-A			
DRAWN	SHAN	JUN./24th/25	$\phi 25.4$ mm, $f=150.5$ mm PLANO CONVEX LENS AR COATING 350–700 nm			
APPROVAL	WCHENG	JUN./24th/25	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			UVFS	3.20g	2:1	B