



NOTES:

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350-700 nm
3. DIAMETER TOLERANCE: $+0.0/-0.1\text{ mm}$
4. THKKNES TOLERANCE: $\pm 0.1\text{ mm}$
5. FOCAL LENGTH: $f=200.7\text{ mm}\pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=196.2\text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8\text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8\text{ nm}$
11. SURFACE RRREGULARITY(S2): $\lambda/4 @ 632.8\text{ nm}$
12. CENTRATION: $<3\text{ arcmin}$
13. CHAMFER: $<0.2\text{mm}, 45^\circ$
14. AR COATING(S1, S2): $R_{avg}<0.5\% @ 350-700\text{ nm}$ (6° AOI , single)

DRAWING PROJECTION			LBTEK			
	NAME	DATE				
DRAWN	AGAO	MAY./26th/25	PLANO CONVEX LENS			
APPROVAL	SHAN	MAY./26th/25	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			UVFS	21.42 g	2:1	A