



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 700 nm–1100 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=100.0 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=96.6 \text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1, S2): 60/40
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8 \text{ nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: $<3 \text{ arcmin}$
13. CHAMFER: $<0.2 \text{ mm}, 45^\circ$
14. COATING(S1, S2): AR COATING $R_{avg} < 0.5\% @ 700 \text{ nm} - 1100 \text{ nm}$

DRAWING PROJECTION			LBTEK			
	NAME	DATE	CY107R14-B			
DRAWN	BSHU	Aug./19th/24	$\phi 25.4 \text{ mm}, f=100 \text{ mm}$ PLANO CONVEX CYLINDRICAL LENS AR COATING 700–1100 nm			
APPROVAL	WCHENG	Aug./19th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	2.79 g	2:1	D