



NO.	PART	MATERIAL
①	∅0.6″ HOLLOW RETROREFLECTOR MIRROR PROTECTED GOLD	UVFS
②	RETROREFLECTOR MOUNT	STAINLESS STEEL
③	M3 HEX SOCKET LOCKING SCREWS WITH NYLON HEADS ×1	STAINLESS STEEL
④	0.5—INCH OPTICAL COMPONENT MOUNTING ADAPTER, WITH SM05 EXTERNAL THREADS, WITH ENGRAVING	ANODIZED ALUMINUM









NOTE:

1. OPERATION WAVELENGTH: 450 nm—20 μm
2. SUBSTRATE MATERIAL: UVFS
3. Substrate THICKNESS: 5 mm
4. CLEAR APERTURE: ∅15.24 mm (∅0.6″)
5. SURFACE QUALITY: 60/40
6. SURFACE FLATNESS: <2λ@633 nm
7. BEAM DEVIATION: <20 arcsec
8. COATING: PROTECTED GLOD
   Ravg>96.0%@800 nm—20 μnm, 0° —45° AOI

DRAWING PROJECTION			LBTEK			
	NAME	DATE	HR206—AU			
DRAWN	LTAN	Apr./10th/26	HOLLOW RETROREFLECTOR MIRROR ∅0.6″, SM05, AU: 800 nm—20 μm			
APPROVAL	WCHEN	Apr./10th/26	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N/A	16 g	2:1	A