



	PART DESCRIPTION	MATERIAL
①	SM1-12.5A	ANODIZED ALUMINIUM
②	AD410-C	N-BAF10
		N-SF6
③	SM1R	ANODIZED ALUMINIUM



NOTES

- MATERIAL: N-BAF10/N-SF6
- DESIGN WAVELENGTH: 1016 nm, 1330 nm & 1550 nm
- CLEAR APERTURE: >90%CA
- OPERATION WAVELENGTH: 1100 nm-1650 nm
- DIAMETER TOLERANCE: +0.0/-0.1 mm
- THICKNESS TOLERANCE: ± 0.2 mm
- FOCAL LENGTH: 150.0 mm $\pm 1\%$ @1330 nm
- BACK FOCAL LENGTH(REF): 140.8 mm
- SURFACE QUALITY (S/D) (S1,S2) : 40/20
- SURFACE POWER (S1,S2) : $3\lambda/2$ @632.8 nm
- SURFACE IRREGULARITY(S1,S2): $\lambda/4$ @632.8 nm
- CENTRATION: <3 arcmin
- CHAMFER: <0.5 mm, 45°
- AR COATING (S1,S2) : $R_{avg} < 0.5\%$ @1100 nm-1650 nm (6° AOI, single)

DRAWING PROJECTION			LBTEK			
		NAME	DATE	MAD410-C		
DRAWN	SHAN	MAY./7th/25	ACHROMATIC DOUBLETS			
APPROVAL	WCHENG	MAY./7th/25	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N/A	20.24 g	2:1	A