



NOTES

1. DESIGN WAVELENGTH: 706.5 nm, 855.0 nm & 1015.0 nm
2. CLEAR APERTURE: >90%CA
3. OPERATION WAVELENGTH: 700 nm-1100 nm
4. DIAMETER TOLERANCE: +0.0/-0.1 mm
5. THICKNESS TOLERANCE: ±0.1 mm
6. FOCAL LENGTH: 300.0 mm ±1% @ 855.0 nm
7. BACK FOCAL LENGTH(REF): 290.0 mm
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE POWER(S1, S2):  $3\lambda/2$  @ 632.8 nm
10. SURFACE IRREGULARITY(S1, S2):  $\lambda/4$  @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1, S2): AR COATING  $R_{avg} < 0.5\%$  @ 700 nm-1100 nm

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	AD413-B	SF5 N-SF6HT
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION			<b>LBTEK</b>			
	NAME	DATE	MAD413-B			
DRAWN	BSHU	Aug./5th/24	$\phi$ 25.4 mm, F=300.0 mm ACHROMATIC DOUBLETS AR COATING 700-1100 nm			
APPROVAL	WCHENG	Aug./5th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			SF5/N-SF6HT	40.18g	2:1	B