



NOTES

1. DESIGN WAVELENGTH: 706.5 nm, 855.0 nm & 1015.0 nm
2. CLEAR APERTURE: >90%CA
3. OPERATION WAVELENGTH: 700 nm-1100 nm
4. DIAMETER TOLERANCE: +0.0/-0.1 mm
5. THICKNESS TOLERANCE: ±0.1 mm
6. FOCAL LENGTH: 40.0 mm ± 1% @ 855.0 nm
7. BACK FOCAL LENGTH(REF): 32.8 mm
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE POWER(S1, S2): $3\lambda/2$ @ 632.8 nm
10. SURFACE IRREGULARITY(S1, S2): $\lambda/4$ @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1, S2): AR COATING R_{avg} < 0.5% @ 700 nm-1100 nm

	PART DESCRIPTION	MATERIAL
①	SM1-16.5A	ANODIZED ALUMINIUM
②	AD415-B	N-BAF10
		N-SF6HT
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION				LBTEK			
				MAD415-B			
DRAWN	BSHU	DATE	Aug./5th/24	ϕ 25.4 mm, F=40.0 mm ACHROMATIC DOUBLETS AR COATING 700-1100 nm			
APPROVAL	WCHENG	DATE	Aug./5th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES				N-BAF10/N-SF6HT	72.06g	2:1	B