



	PART DESCRIPTION	MATERIAL
①	SM1-16.5A	ANODIZED ALUMINIUM
②	AD417-C	N-LAK22
		N-SF6
③	SM1R	ANODIZED ALUMINIUM



NOTES

- MATERIAL: N-LAK22/N-SF6
- DESIGN WAVELENGTH: 1016 nm, 1330 nm & 1550 nm
- CLEAR APERTURE: >90%CA
- OPERATION WAVELENGTH: 1100 nm-1650 nm
- DIAMETER TOLERANCE: +0.0/-0.1 mm
- THICKNESS TOLERANCE:  $\pm 0.2$  mm
- FOCAL LENGTH: 60.0 mm  $\pm 1\%$ @1330 nm
- BACK FOCAL LENGTH(REF): 50.5 mm
- SURFACE QUALITY (S/D) (S1,S2) : 40/20
- SURFACE POWER (S1,S2) :  $3\lambda/2$ @632.8 nm
- SURFACE IRREGULARITY(S1,S2):  $\lambda/4$ @632.8 nm
- CENTRATION: <3 arcmin
- CHAMFER: <0.2 mm, 45°
- AR COATING (S1,S2) :  $R_{avg} < 0.5\%$ @1100 nm-1650 nm (6° AOI, single)

DRAWING PROJECTION							
	NAME	DATE		ACHROMATIC DOUBLETS			
DRAWN	SHAN	MAY./7th/25		MATERIAL	WEIGHT	SCALE	REV
APPROVAL	WCHENG	MAY./7th/25		N/A	14.25 g	2:1	A
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES							