



	PART DESCRIPTION	MATERIAL
①	SM2-25A	ANODIZED ALUMINIUM
②	AD512-A	E-BAF11
		N-SF11
③	SM2R	ANODIZED ALUMINIUM



NOTES

1. MATERIAL: E-BAF11/N-SF11
2. DESIGN WAVELENGTH: 486.1 nm, 587.6 nm & 656.3 nm
3. CLEAR APERTURE: >90%CA
4. OPERATION WAVELENGTH: 400 nm-700 nm
5. DIAMETER TOLERANCE: +0.0/-0.1 mm
6. THICKNESS TOLERANCE: ±0.2 mm
7. FOCAL LENGTH: 75.0 mm ±1%@587.6 nm
8. BACK FOCAL LENGTH(REF): 61.8 mm
9. SURFACE QUALITY (S/D) (S1,S2) : 40/20
10. SURFACE POWER (S1,S2) : $3\lambda/2@632.8$ nm
11. SURFACE IRREGULARITY(S1,S2): $\lambda/4@632.8$ nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING (S1,S2) : AR COATING $R_{avg}<0.5%@400$ nm-700 nm

DRAWING PROJECTION			LBTEK			
NAME		DATE				
DRAWN	BSHU	Aug./5th/24	$\Phi 50.8$ mm, F=75.0 mm ACHROMATIC DOUBLETS AR COATING 400-700 nm			
APPROVAL	WCHENG	Aug./5th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			E-BAF11/N-SF11	123.79g	1:1	B