



	PART DESCRIPTION	MATERIAL
①	SM2-16.5A	ANODIZED ALUMINIUM
②	AD513-C	N-BAF10
		N-SF6HT
③	SM2R	ANODIZED ALUMINIUM



NOTES

1. MATERIAL: N-BAF10/N-SF6HT
2. DESIGN WAVELENGTH: 1016.0 nm, 1330.0 nm & 1550.0 nm
3. CLEAR APERTURE: >90%CA
4. OPERATION WAVELENGTH: 1100 nm-1650 nm
5. DIAMETER TOLERANCE: +0.0/-0.1 mm
6. THICKNESS TOLERANCE: ±0.2 mm
7. FOCAL LENGTH: 300.0 mm ±1%@1330.0 nm
8. BACK FOCAL LENGTH(REF): 287.6 mm
9. SURFACE QUALITY (S/D) (S1,S2): 40/20
10. SURFACE POWER (S1,S2): $3\lambda/2@632.8$ nm
11. SURFACE IRREGULARITY(S1,S2): $\lambda/4@632.8$ nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING (S1,S2): AR COATING $R_{avg}<0.5%@1100$ nm-1650 nm

DRAWING PROJECTION				LBTEK			
	NAME	DATE	MAD513-C				
DRAWN	BSHU	Aug./5th/24	$\phi 50.8$ mm, F=300.0 mm ACHROMATIC DOUBLETS AR COATING 1100-1650 nm				
APPROVAL	WCHENG	Aug./5th/24	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BAF10/N-SF6	82.09g	2:1	B	