



	PART DESCRIPTION	MATERIAL
①	SM2-12.5A	ANODIZED ALUMINIUM
②	AD520-B	N-LAK22
		N-SF6HT
③	SM2R	ANODIZED ALUMINIUM



NOTES

1. MATERIAL: N-LAK22/N-SF6HT
2. DESIGN WAVELENGTH: 706.5 nm, 855 nm & 1015 nm
3. CLEAR APERTURE: >90%CA
4. OPERATION WAVELENGTH: 700 nm-1100 nm
5. DIAMETER TOLERANCE: +0.0/-0.1 mm
6. THICKNESS TOLERANCE: ±0.2 mm
7. FOCAL LENGTH: 400.0 mm ±1%@855 nm
8. BACK FOCAL LENGTH(REF): 393.6 mm
9. SURFACE QUALITY (S/D) (S1,S2) : 40/20
10. SURFACE POWER (S1,S2) :  $3\lambda/2@632.8\text{ nm}$
11. SURFACE IRREGULARITY(S1,S2):  $\lambda/4@632.8\text{ nm}$
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. AR COATING (S1,S2) :  $R_{avg}<0.5\%@700\text{ nm}-1100\text{ nm}$  (6° AOI, single)

DRAWING PROJECTION				<h1 style="color: red; margin: 0;">LBTEK</h1>					
		NAME		DATE		MAD520-B			
DRAWN		SHAN		MAY./7th/25		ACHROMATIC DOUBLETS			
APPROVAL		WCHENG		MAY./7th/25		MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES						N/A	57.56g	1:1	A