



	PART DESCRIPTION	MATERIAL
①	SM2-12.5A	ANODIZED ALUMINIUM
②	AD528-B	N-BAF10
		N-SF10
③	SM2R	ANODIZED ALUMINIUM



NOTES

- MATERIAL: N-BAF10/N-SF10
- DESIGN WAVELENGTH: 706.5 nm, 855 nm & 1015 nm
- CLEAR APERTURE: >90%CA
- OPERATION WAVELENGTH: 700 nm-1100 nm
- DIAMETER TOLERANCE: +0.0/-0.1 mm
- THICKNESS TOLERANCE: ±0.2 mm
- FOCAL LENGTH: 750.0 mm ±1%@855 nm
- BACK FOCAL LENGTH(REF): 745 mm
- SURFACE QUALITY (S/D) (S1,S2) : 40/20
- SURFACE POWER (S1,S2) : $3\lambda/2@632.8\text{ nm}$
- SURFACE IRREGULARITY(S1,S2): $\lambda/4@632.8\text{ nm}$
- CENTRATION: <3 arcmin
- CHAMFER: <0.2 mm, 45°
- AR COATING (S1,S2) : $R_{avg}<0.5\%@700\text{ nm}-1100\text{ nm}$ (6° AOI, single)

DRAWING PROJECTION				<h1 style="color: red; margin: 0;">LBTEK</h1>			
	NAME	DATE		ACHROMATIC DOUBLETS			
DRAWN	SHAN	MAY./7th/25		MATERIAL	WEIGHT	SCALE	REV
APPROVAL	WCHENG	MAY./7th/25		N/A	57.54g	1:1	A
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES							