



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm-700 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: 25.0 mm±1%
6. BACK FOCAL LENGTH(REF): 23.8 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1.S2): 40/20
9. SURFACE POWER(S2):  $3\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE IRREGULARITY(S2):  $\lambda/4 @ 632.8 \text{ nm}$
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): AR COATING  $R_{avg} < 0.5\% @ 400 \text{ nm}-700 \text{ nm}$

	PART DESCRIPTION	MATERIAL
①	SM05-8A	ANODIZED ALUMINIUM
②	BCX10305-A	N-BK7
③	SM05R	ANODIZED ALUMINIUM

DRAWING PROJECTION				<b>LBTEK</b>					
		NAME		DATE		MBCX10305-A			
DRAWN		BSHU		Aug./19th/24		$\phi 12.7 \text{ mm}, F=25.0 \text{ mm}$ BI-CONVEX LENS AR COATING 400-700 nm			
APPROVAL		WCHENG		Aug./19th/24		MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES						N-BK7	9.22 g	2:1	B