



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350 nm-2.0 μ m
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: \pm 0.1 mm
5. FOCAL LENGTH: 60.0 mm \pm 1%
6. BACK FOCAL LENGTH(REF): 58.4 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE POWER(S2): $3 \lambda / 2$ @ 632.8 nm
10. SURFACE IRREGULARITY(S2): $\lambda / 4$ @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1, S2): UNCOATED

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	BCX10611	N-BK7
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION			LBTEK			
			MBCX10611			
			ϕ 25.4 mm, F=60.0 mm BI-CONVEX LENS UNCOATED			
	NAME	DATE	MATERIAL	WEIGHT	SCALE	REV
DRAWN	BSHU	Aug. /19th/24				
APPROVAL	WCHENG	Aug. /19th/24				
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	22.02g	2:1	B