



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 200 nm-2.1 μ m
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: \pm 0.1 mm
5. FOCAL LENGTH: 50.0 mm \pm 1%
6. BACK FOCAL LENGTH(REF): 48.0 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2): $3\lambda/2$ @ 632.8 nm
10. SURFACE IRREGULARITY(S2): $\lambda/4$ @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): UNCOATED

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	BCX20613	UV FUSED SILICA
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION				LBTEK					
		NAME		DATE		MBCX20613			
DRAWN		BSHU		Aug./19th/24		ϕ 25.4 mm, F=50.0 mm BI-CONVEX LENS UNCOATED			
APPROVAL		WCHENG		Aug./19th/24		MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES						UVFS	22.23g	2:1	B