



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 200 nm-8.0  $\mu$ m
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE:  $\pm$ 0.1 mm
5. FOCAL LENGTH: 200.0 mm $\pm$ 1%
6. BACK FOCAL LENGTH(REF): 199.0 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE POWER(S2):  $3\lambda/2$  @ 632.8 nm
10. SURFACE IRREGULARITY(S2):  $\lambda/4$  @ 632.8 nm
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): UNCOATED

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	MBCX70621	CAF2
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION			<b>LBTEK</b>				
		MBCX70621					
		D=25.4 mm, f=200.0 mm BI-CONVEX LENS Uncoated					
DRAWN	BSHU	DATE	Aug./19th/24	MATERIAL	WEIGHT	SCALE	REV
APPROVAL	WCHENG	DATE	Aug./19th/24	CaF2	19.15g	2:1	B
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES							