



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350 nm-2.0 μm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: 40.0 mm±1%
6. BACK FOCAL LENGTH(REF): 36.3 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 20/10
9. SURFACE POWER(S2): $3\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
11. CENTRATION: <3 arcmin
12. CHAMFER: <0.2 mm, 45°
13. COATING(S1,S2): UNCOATED

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	BFCX10609	N-BK7
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION				LBTEK			
NAME		DATE		MBFCX10609			
DRAWN		BSHU		Aug./19th/24		$\phi 25.4 \text{ mm}, F=40.0 \text{ mm}$ BEST FORM LENS UNCOATED	
APPROVAL	WCHENG	Aug./19th/24	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	23.23g	2:1	B	