



| | PART DESCRIPTION | MATERIAL |
|---|------------------|--------------------|
| ① | SM1-12.5A | ANODIZED ALUMINIUM |
| ② | CC10610-A | N-BK7 |
| ③ | SM1R | ANODIZED ALUMINIUM |



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm-700 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: -50.0 mm±1%
6. BACK FOCAL LENGTH(REF): -52.3 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2$ @ 632.8 nm
10. SURFACE POWER(S2): $3\lambda/2$ @ 632.8 nm
11. SURFACE IRREGULARITY(S2): $\lambda/4$ @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): AR COATING Ravg <0.5% @ 400 nm-700 nm

| | | | | | | |
|--|--------|--------------|---|--------|-------|-----|
| DRAWING PROJECTION | | | LBTEK | | | |
| | | | | | | |
| | NAME | DATE | MCC10610-A | | | |
| DRAWN | BSHU | Aug./19th/24 | ϕ 25.4 mm, f=-50.0 mm PLANO CONCAVE LENS AR COATING 400-700 nm | | | |
| APPROVAL | WCHENG | Aug./19th/24 | MATERIAL | WEIGHT | SCALE | REV |
| FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES | | | N-BK7 | 30.70g | 2:1 | B |