



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 400 nm-1100 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: $f=50.0 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF): $bf=48.1 \text{ mm}$
7. CLEAR APERTURE: $>90\%CA$
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2): $3\lambda/2 @ 632.8 \text{ nm}$
11. SURFACE IRREGULARITY(S2): $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: $<3 \text{ arcmin}$
13. CHAMFER: $<0.2 \text{ mm}, 45^\circ$
14. COATING(S1,S2): AR COATING $R_{avg} < 1\% @ 400 \text{ nm}-1100 \text{ nm}$

	PART DESCRIPTION	MATERIAL
①	SM05-8A	ANODIZED ALUMINIUM
②	CX10310-AB	N-BK7
③	SM05R	ANODIZED ALUMINIUM

DRAWING PROJECTION			LBTEK			
			MCX10310-AB			
DRAWN	BSHU	Aug./12th/24	N-BK7, D=12.7 mm, f=50.0 mm PLANO CONVEX LENS AR: 400 nm-1100 nm			
APPROVAL	WCHENG	Aug./12th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	3.92 g	3:1	B