



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350 nm-2.0 μ m
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: \pm 0.1 mm
5. FOCAL LENGTH: $f=25.4$ mm \pm 1%
6. BACK FOCAL LENGTH(REF): $bf=17.6$ mm
7. CLEAR APERTURE: $>90\%$ CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): $\lambda/2$ @ 632.8 nm
10. SURFACE POWER(S2): $3\lambda/2$ @ 632.8 nm
11. SURFACE IRREGULARITY(S2): $\lambda/4$ @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): UNCOATED

	PARTDESCRIPTION	MATERIAL
①	SM1-12.5A	ANODIZED ALUMINIUM
②	CX10606	N-BK7
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION		LBTEK				
		MCX10606				
		$\phi 25.4$ mm, $f=25.4$ mm PLANO CONVEX LENS UNCOATED				
	NAME	DATE	MATERIAL	WEIGHT	SCALE	REV
DRAWN	BSHU	Aug./5th/24				
APPROVAL	WCHENG	Aug./5th/24	N-BK7	34.33g	2:1	B
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES						