



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 350 nm-2.0 μm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH: f=40.0 mm±1%
6. BACK FOCAL LENGTH(REF): bf=35.7 mm
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1): λ/2 @ 632.8 nm
10. SURFACE POWER(S2): 3 λ/2 @ 632.8 nm
11. SURFACE IRREGULARITY(S2): λ/4 @ 632.8 nm
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): UNCOATED

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	CX10609	N-BK7
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION		LBTEK				
		MCX10609				
DRAWN		BSHU	DATE		Aug./5th/24	
APPROVAL		WCHENG	DATE		Aug./5th/24	
		Ø25.4 mm, f=40 mm PLANO CONVEX LENS UNCOATED				
		FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES	MATERIAL	WEIGHT	SCALE	REV
			N-BK7	23.36g	2:1	B