



NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 700 nm-1100 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH:  $f=100.0 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF):  $bf=97.3 \text{ mm}$
7. CLEAR APERTURE: >90%CA
8. SURFACE QUALITY(S/D)(S1,S2): 40/20
9. SURFACE FLATNESS(S1):  $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2):  $3 \lambda/2 @ 632.8 \text{ nm}$
11. SURFACE IRREGULARITY(S2):  $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION: <3 arcmin
13. CHAMFER: <0.2 mm, 45°
14. COATING(S1,S2): AR COATING  $R_{avg} < 0.5\% @ 700 \text{ nm}-1100 \text{ nm}$

	PARTDESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	CX10613-B	N-BK7
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION				<b>LBTEK</b>			
	NAME	DATE	MCX10613-B				
DRAWN	BSHU	Aug./12th/24	$\phi 25.4 \text{ mm}, f=100 \text{ mm}$ PLANO CONVEX LENS AR COATING 700-1100 nm				
APPROVAL	WCHENG	Aug./12th/24	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	19.32g	2:1	B	