


NOTES

1. DESIGN WAVELENGTH: 587.6 nm
2. OPERATION WAVELENGTH: 1100 nm-1650 nm
3. DIAMETER TOLERANCE: +0.0/-0.1 mm
4. THICKNESS TOLERANCE: ±0.1 mm
5. FOCAL LENGTH:  $f=150.0 \text{ mm} \pm 1\%$
6. BACK FOCAL LENGTH(REF):  $bf=147.5 \text{ mm}$
7. CLEAR APERTURE:  $>90\%CA$
8. SURFACE QUALITY(S/D)(S1, S2): 40/20
9. SURFACE FLATNESS(S1):  $\lambda/2 @ 632.8 \text{ nm}$
10. SURFACE POWER(S2):  $3 \lambda/2 @ 632.8 \text{ nm}$
11. SURFACE IRREGULARITY(S2):  $\lambda/4 @ 632.8 \text{ nm}$
12. CENTRATION:  $<3 \text{ arcmin}$
13. CHAMFER:  $<0.2 \text{ mm}, 45^\circ$
14. COATING(S1, S2): AR COATING  $R_{avg} <0.5\% @ 1100 \text{ nm}-1650 \text{ nm}$

	PART DESCRIPTION	MATERIAL
①	SM1-8A	ANODIZED ALUMINIUM
②	CX10615-C	N-BK7
③	SM1R	ANODIZED ALUMINIUM

DRAWING PROJECTION



**LBTEK**

NAME		DATE	MCX10615-C			
DRAWN	BSHU	Aug./12th/24	$\phi 25.4 \text{ mm}, f=150 \text{ mm}$ PLANO CONVEX LENS AR COATING 1100-1650 nm			
APPROVAL	WCHENG	Aug./12th/24	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES			N-BK7	19.20g	2:1	B